

Contract Numbers: GM - #706-23 CF - #685-22

KX057-5R3AP WEB QUOTE #2818335 Date: 10/7/2024 2:53:49 PM

- Customer Information -JACKS, TRICIA SABINE COUNTY PCT 1 treasurer@co.sabine.tx.us

409-787-2210

Quote Provided By WC Tractor CHARLES PERKINS 10044 Hwy. 6 South Navasota, TX 77868 email:

CHARLES.PERKINS@WCTRACTOR.COM phone: 9364651382

- Custom Options --

Standard Features -



* * * EQUIPMENT IN STANDARD MACHINE * * *

FEATURES

7" LCD Color Display Auto Idler Rubber Track Models A/C ROPS/OPG Cab Kubota 3 Hydraulic Pump Load OPERATIONAL Sensing System 1 Gear, 2 Variable Displacement Pumps All Controls Hydraulic Pilot Controls

Two Operating Pattern Selection System Accumulator

Digital Control Panel Attachment Flow Presets. Service Alerts

Standard Front Dozer Blade w/ Float

360 Degree Full Rotation 70 Degree Left, 55 Degree Right Boom Swing 19 8 gpm Adjustable Auxiliary Hydraulics Port 1

Auxiliary Hydraulics Diverter Valve Thumb Bracket and Relief

Valves Five Second Quick Preheat System

Key Switch Stop System Half Pitch Rubber Tracks Self Bleed Fuel System Auto-Downshift Two Speed Travel System

Swivel Negative Brake Travel Negative Brake Third Line

DIMENSIONS AND OPERATING WEIGHT KX057-5R3AP, Rubber Tracks ROPS/OPG (Top Guard, Level I) Cab, Angle Dozer Blade, Dipper Arm, Counterweight, SP2

Overall Length 18' 1.3" Overall Width 6' 5.2" Overall Height 8' 4.4" Operating Weight 13,051 lbs.* Ground Clearance 12' 0.2"

*Includes operator's weight, 165 lbs

ENGINE

V2607 Kubota CR E5 Tier 4 Diesel Engine 4 Cylinder, 4 Cycle 46.4 Net HP @ 2200 rpm (SAE J1349)

DIMENSIONS

Max Digging Depth 12' 9" Max Digging Radius @ Ground Level 20' 1" Max Vertical Digging Depth 5' 4" Max Dumping Height 13' 8.6"

DOZER BLADE **DIMENSIONS** Width 77 2"

Height 16.1" Lift Above Ground 17.3" Drop Below Ground 15.9"

PERFORMANCE

Digging Force @ Bucket 10,172 lbs Digging Force @ Dipper Arm 5,463 lbs. Travel Speed (Low) 1.7 mph Travel Speed (High) 3.0 mph Climbing Ability 36% / 20° Lift Capacity 3,410 lbs. Over Front Blade Grounded 4.0 Ft. Load Point Height 12.0 Ft. Load Radius

STANDARD WARRANTY

Basic Warranty - 24 Months / 2000 Hours Rubber Track Warranty - 12 Months / 1000 Hours

\$93,901.00 KX057-5R3AP Base Price: (1) 24" QUICK ATTACH TRENCHING BUCKET \$1,885.00 K7919-24" QUICK ATTACH TRENCHING BUCKET (1) QUICK ATTACH COUPLER \$1,349.00 K7915-QUICK ATTACH COUPLER (1) 36" QUICK ATTACH DRAINAGE BUCKET \$2,022.00 K7922-36" OUICK ATTACH DRAINAGE BUCKET (1) AT&T TELEMATICS MODEM \$449.00 DCU6700-AT&T TELEMATICS MODEM (1) EXCAVATOR & WL TELEMATICS HARNESS \$162.00 K6704A-EXCAVATOR & WL TELEMATICS HARNESS (1) Hydraulic Thumb \$3,327.00 K7937B-Hydraulic Thumb (1) TRAVEL ALARM KIT \$196.00 K7278-TRAVEL ALARM KIT \$103.291.00 Configured Price: BUY BOARD Discount: (\$24,789.84)SUBTOTAL: \$78.501.16 2Yr KX057-5R3AP Extended Warranty \$3,000.00

> Total Unit Price: \$82,985.83 Quantity Ordered: Final Sales Price: \$82,985.83

\$234.67

\$850.00

\$400.00

Purchase Order Must Reflect the Final Sales Price

To order equipment - purchase orders must be made out and

Kubota Tractor Corporation Attn: National Accounts 1000 Kubota Drive Grapevine, TX 76051 or email NA.Support@kubota.com or call 817-756-1171 or fax 844-582-1581

Dealer Assembly:

Freight Cost:

PDI:

*All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.

© 2018 Kubota Tractor Corporation, All rights reserved

Excaptor) al boello

Vol 4-D Page 38